

30 kW Pitch Control Wind Turbine

ROCKSOLAR | RS-PCWT-30KW

Three-blade, horizontal-axis wind turbine with mechanical centrifugal pitch control and active yaw alignment.

30 kW

Rated power

13.1 m

Rotor diameter

12 m/s

Rated wind speed



OUTPUT AND WIND CONDITIONS	
Rated output	30 kW at 12 m/s
Rated rotor speed	105 rpm
Start-up / cut-in wind speed	2.5 m/s / 3 m/s
Cut-out wind speed	25 m/s
Survival wind speed	59.5 m/s
ROTOR GENERATOR AND CONTROL	
Configuration / design class	Horizontal axis, upwind / IEC Class II*
Rotor diameter	13.1 m
Blade material / quantity	Glass fibre reinforced plastic (GFRP) / 3
Generator / insulation	Three-phase AC permanent magnet synchronous / Class F
Speed regulation	Mechanical centrifugal pitch control
Wind direction alignment	Active yaw
High-wind protection	Pitch control and intelligent brake shutdown
Shutdown sequence	Pitch control followed by mechanical braking
CONSTRUCTION AND OPERATING ENVIRONMENT	
Operating temperature	-25°C to +50°C
Ingress protection	IP54
Turbine weight	2,800 kg
Design life	20 years
Colour	White
TOWER REFERENCE CONFIGURATION	
Tower height options	20 m hub height
Tower material	Q355 steel
Tower structure	Tapered polygonal sections with external flange joints
Corrosion protection	Hot-dip galvanizing

Tower, foundation, controller/inverter and grid interface are project-specific. Confirm package contents and Canadian electrical compatibility with ROCKSOLAR. Actual output depends on wind and site conditions.